


TBL Series





แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE










BLSEMES



แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE 🥩












แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE 🥩







MECHANICAL DRAWINGS:











TECHNICAL SPECIFICATIONS:

Mechanical Specifications

Industry Reference	12V Tubular Flooded		
Length[A]	19.9 in	505 mm	
Width [B]	8.7 in	220 mm	
Height Upto Lid [C1]	8.3 in	212 mm	
Height Upto Dome [D]	9.9 in	256 mm	
Weight (Acid Filled)	79.2 lbs	37 kgs	
Weight (Dry)	44.0 lbs	20 kgs	
Terminal	M8		
Cells	6		
Electrolyte	1.250±0.01 at 27° C		

Electrical Specifications

Capacity @ 27 C	@5 HR	75	AH
	@10 HR	87	AH
	@20 HR	100	AH
Cycle Life	@20% DOD		3000
	@50% DOD		1650
	@80% DOD		1250
RINT			$5m\Omega$
Short Circuit			1250
Self Discharge/per month			4-5%
Maximum Operating Temperature			50°C









FEATURES & BENEFITS:


- Excellent cycling ability provides high reliability and exceptionally long life
- Large electrolyte reservoirmeans high tolerance to water loss and minimal maintenance
- Low internal resistance
- ★ High charging efficiency

- ★ Low self-discharge, pre charged plates
- Robust, rugged constructionensures mechanical durability
- ★ High performed specialized pasting recipe and separator arrangement provides minimal chance of active material shedding
- User friendly with rigid handle arrangement












แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE










แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE 💆



















TBL 1500






แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE รุ่น VINT และ TBL แพ่นธาตุหนากว่าแบตเตอรี่ทั่วไป 5 เท่า พลิตจากวัสดุเกรดพรีเมียม สามารถนำไฟฟ้าได้เป็นอย่างดี มั่นใจได้ในคุณภาพและอายุการใช้งาน คุ้มค่า คุ้มราคา



MECHANICAL DRAWINGS:











TECHNICAL SPECIFICATIONS:

Mechanical Specifications

Industry Reference	12V Tubular Flooded		
Length[A]	20.5 in	520 mm	
Width [B]	10.9 in	277 mm	
Height Upto Lid [C1]	8.3 in	212 mm	
Height Upto Dome [D]	10.1 in	261 mm	
Weight (Acid Filled)	92.4 lbs	43 kgs	
Weight (Dry)	50.6 lbs	24 kgs	
Terminal	M8		
Cells	6		
Electrolyte	1.250±0.01 at 27° C		

Electrical Specifications

Capacity @ 27 C	@5 HR	90	AH
	@10 HR	103	AH
	@20 HR	120	AH
Cycle Life	@20% DOD		3000
	@50% DOD		1650
	@80% DOD		1250
RINT			$5m\Omega$
Short Circuit			1500
Self Discharge/per month			4-5%
Maximum Operating Temperature			50°C









FEATURES & BENEFITS:


- Excellent cycling ability provides high reliability and exceptionally long life
- Large electrolyte reservoirmeans high tolerance to water loss and minimal maintenance
- Low internal resistance
- ★ High charging efficiency

- ★ Low self-discharge, pre charged plates
- Robust, rugged constructionensures mechanical durability
- ★ High performed specialized pasting recipe and separator arrangement provides minimal chance of active material shedding
- User friendly with rigid handle arrangement












แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE










แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE 💆




















TBL 1600










MECHANICAL DRAWINGS:











TECHNICAL SPECIFICATIONS:

Mechanical Specifications

Industry Reference	12V Tubular Flooded		
Length[A]	20.5 in	520 mm	
Width [B]	10.9 in	277 mm	
Height Upto Lid [C1]	8.3 in	212 mm	
Height Upto Dome [D]	10.1 in	261 mm	
Weight (Acid Filled)	110.0 lbs	52 kgs	
Weight (Dry)	70.4 lbs	33 kgs	
Terminal	M8		
Cells	6		
Electrolyte	1.250±0.01 at 27° C		

Electrical Specifications

Capacity @ 27 C	@5 HR	112.3	5 AH
	@10 HR	130	AH
	@20 HR	150	AH
Cycle Life	@20% DOD		3000
	@50% DOD		1650
	@80% DOD		1250
RINT			$5m\Omega$
Short Circuit			1700
Self Discharge/per month			4-5%
Maximum Operating Temperature			50°C







FEATURES & BENEFITS:


- Excellent cycling ability provides high reliability and exceptionally long life
- Large electrolyte reservoirmeans high tolerance to water loss and minimal maintenance
- Low internal resistance
- ★ High charging efficiency

- ★ Low self-discharge, pre charged plates
- Robust, rugged constructionensures mechanical durability
- ★ High performed specialized pasting recipe and separator arrangement provides minimal chance of active material shedding
- User friendly with rigid handle arrangement












แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE









แบตเตอรี่ VOLTA TUBULAR DEEP CYCLE 💆







